

<b>MODÈLE</b>	<b>RFR025</b>	<b>RFR05</b>	<b>RFR07</b>	<b>RFR10-C</b>	<b>RFR10-A</b>	<b>RFR10-HV</b>
Poids (approx)	1628 lb	2 530 lb	2 860 lb	3 500 lb	3 500 lb	3 500 lb
	738 kg	1 147 kg	1 297 kg	1 587 kg	1 587 kg	1 587 kg
GVWR	7700 lb	13 385 lb	16 500 lb	20 000 lb	23 520 lb	23 520 lb
	3 492 kg	6 071 kg	7 484 kg	9 072 kg	10 668 kg	10 668 kg
Surface de Chargement	64" x10'8"	84" x 15'4"	84" x 15'4"	84" x 15'4"	84" x 15'4"	84" x 15'4"
	1,6m x 3,2m	2,1m x 4,6m	2,1m x 4,6m	2,1m x 4,6m	2,1m x 4,6m	2,1m x 4,6m
Longueur hors tout	17.0' / 5,18m	22.0' / 6,7 m	22.0' / 6,7 m	22.0' / 6,7 m	22.0' / 6,7 m	22.0' / 6,7 m
Largeur hors tout	72" / 182cm	89" / 226cm	89" / 226cm	89" / 226cm	89" / 226cm	89" / 226cm
Suspension	Lames	Lames	lames	Lames	Lames	Lames
Freins électriques	10" / 25cm	12" / 30cm	12" / 30cm	12" / 30cm	12" / 30cm	12" / 30cm
Pneus	H78/15ST	235/85R16	235/85R16	235/85R16	235/85R16	235/85R16
	8 plis	10 plis	14 plis	14 plis	14 plis	14 plis
Poteau	8 x 48"	8 x 48"	8 x 48"	8 x 48"	8 x 48"	8 x 48"
	8 x 121cm	8 x 121cm	8 x 121cm	8 x 121cm	8 x 121cm '	8 x 121cm
Sangle d'arrimage	2	4	4	4	4	4
Hauteur coupleur	18" / 45,7 cm	21" / 53,3	21" / 53,3	21" / 53,3	21" / 53,3	21" / 53,3
Voie centre/centre pneu	50" / 127cm	71" / 180,3cm	71" / 180,3cm	71" / 180,3cm	71" / 180,3cm	71" / 180,3cm
Moyeu qté/boulons	5	8	8	8	8	8
Main d'attache	2-5/16" / 5,7cm	2-5/16" / 5,7cm	2-5/16" / 5,7cm	2-5/16" / 5,7cm	Anneau	2-5/16" / 5,7cm
Anneau	OPT	OPT	OPT	-	STD	-
<b>OPTION</b>						
Pneu de secours	H78/15ST	235/85R16	235/85R16	235/85R16	235/85R16	235/85R16
	8 Plis	10 Plis	14 Plis	14 Plis	14 Plis	14 Plis
Gooseneck-1	OPT	OPT	OPT	OPT	OPT	OPT

