

SPECIFICATIONS GENERALES REMORQUE BASCULANTE ROUTIÈRE

Modèle	AM 480-285	AM 510-700	AM 610-1000	AM 612-1200	AM 614-1400	AM 616-1400	AM 616-2000
Poids (approx) lb	1350	1865	1925	2350	2650	3 100	3400
PNBV(GVWR) lb	2850	7 000	10000	12000	14000	14000	20000
CapaCite (pi ³)	53	83	100	120	140	160	160
Surface de Chargement	50" x 97"	60" x 120"	72" x 120"	72" x 142 /12"	72" x 168"	72" x1 92"	72" x 192"
Longueur hors-tout	147"	172 1/2"	172 1/2"	197"	221 "	245"	245"
Largeur hors-tout	70"	82 1/2"	94 1/2"	94 1/2"	94 1/2"	94 1/2"	94 1/2"
Hauteur coupleur	13"	15"	15"	15"	20"	20"	20"
Hauteur des côtes	20"	20"	20"	20"	20"	20"	20"
V oie c. c. pneu	60"	72"	84"	84"	84"	84"	84"
Essieu/diamètre	1.900"(2)	2 3/8"(2)	3"(2)	3"(2)	3" (2)	3" (2)	3" (3)
Quantité boulons	5	5	6	8	8	8	8
Suspension (Lames)	std	std	std	std	sid	sid	std
Pneu	175/80D13	225/75D15	225/75D15	235/85R16	235/85R16	235/85R16	235/85R16
Panneau arrière	Battant double	Battant double	Battant double	Battant double	Battant double	Battant double	Battant double
Main d' attache	2"	2 5/16"	2 5/16"	2 5/16"	2 5/16"	2 5/16"	2 5/16"
Unité hyd. 12 volts	Inc	Inc.	Inc.	Inc.	Inc.	Inc.	Inc.
Frein électrique	Opt 7"	Inc 10"	Inc 12"	Inc 12"	Inc 12"	Inc 12"	Inc 12"
Cylindre	Dessous 3" x 16" (1)	Dessous 3" x 16" (2)	Dessous 3" x 16"(2)	Télescopique	Télescopique	Télescopique	Télescopique
Verin	Inc.	Inc.	Inc.	Inc.	Inc.	Inc.	Inc.
Coffret pour batterie	Inc.	Inc.	Inc.	Inc.	Inc.	Inc.	Inc.
Batterie	Inc.	Inc.	Inc.	Inc.	Inc.	Inc.	Inc.
Coffret de rangement	opt.	Inc.	Inc.	Inc.	Inc.	Inc.	Inc.
Support pour pneu de secours	Inc.	Inc.	Inc.	Inc.	Inc.	Inc.	Inc.
Options							
Goose Neek	ND	ND	opt.	opt.	opt.	opt.	opt.
Toile et tige	opt	opt.	opt.	opt.	opt.	opt.	opt.
Rampe de chargement	opt.	opt.	opt.	opt.	opt.	opt.	opt.
Chargeuses							
900 SR	X						
JMS 110		X	X				
JMS 130			X	X	X		
JMS 155				X	X	X	X
JMS 170					X	X	X
Unité hydraulique	5.5HP	5.5HP/9HP	5.5HP/9HP	9HP/11HP	9HP/11HP	9HP/11HP	9HP/11J-IP